



□□□□□□□□□□□□□□□□□□□□□□□□□□□□

**Size:24\*14\*8mm\*2T**



**M6 or M8 or Bare Holes**

**Application: Concrete and Terrazzo Floor**

**<Trapezoid Grinding Shoes>**



**3 X M6/M8 Thread Holes**




**3 X Bare Holes**

□□□□

1. M6

2. M8

3.






# Concrete Floor Grinding

METAL BOND DIAMOND GRINDING PLATES FOR HTC, LAVINA, HUSQVARNA CONNECTION:

The collage illustrates the grinding process from tool preparation to the final polished result. It shows diamond grinding plates, a grinding machine head, a full machine in use, and the resulting smooth floor surface.



CONCRETE HARDNESS	Xtreme Hard	Very Hard	Hard	Medium Hard	Soft	Very Soft
PSI	6500–9000	5000–7000	4000–5000	3000–4000	1500–3500	1000–2000
MPA	C50–C65	C40–C55	C30–C50	C20–C40	C15–C25	C10–C20
CODE	XHF	VHF	HF	MHF	SF	VSF
COLOUR						

□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□





1.

2.

3.



Boreway Machinery Co.,Ltd  
www.diamondtools.top  
www.boreway.net

Boreway Machinery Co.,Ltd  
www.diamondtools.top  
www.boreway.net

Boreway Machinery Co.,Ltd  
www.diamondtools.top  
www.boreway.net



□□□□□□

1. □□□□□□□□□□□□□□□□□□□□
2. □ □□□□□□□□□□□□□□□□□□□
3. OEM □□□□□□□□□□□□□□□□□□□□
4. □□□□□□□□□□□□□□□□□□□□□□□□
5. □ □□□□□□□□□□□□□□□□□□□□□□□

□□□

1. □□□□□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□□□  
 □□□□□□8□□□□□□□□□□□□□□□□□□□

