

**Introduction:**

This product use the computer touch screen control, human-machine interface operation. Automatic control of welding time, sink with matrix photoelectric detection system, body automatic positioning. Automatically send segment, automatic rotation blockbusters, automatic sending welding wire, high positioning accuracy, tooth at the end of the second sending welding wire, guarantee the final welding strength. Bilateral independent fan, cooling speed. Automatic alarm display, convenient and troubleshooting. A high degree of automation, simple operation, can automatically complete all welding process.

**Specifications:**

The followings are the normal specifications of our BWM-CY80A automatic welding frame for diamond saw blade:

Welding Diameter	mm	Φ280-Φ800
Welding error□Verticality□	mm	±0.03
Welding Capacity□pc/h□	Pc/h	250-800
Air Pressure	Mpa	0.6
Hydraulic Pressure	Mpa	0.2
Power	W	2200
Water Consumption	m <sup>3</sup> /h	1.5
Weight	Kg	230
Size	mm	1000*810*1550

**usage scenario:**



**We also have :**

[2300mm saw blade welding machine frame / rack,](#)  
[1400mm saw blade welding machine frame / rack,](#)  
[1200mm saw blade welding machine frame / rack,](#)  
[2200mm saw blade welding machine frame / rack.](#)