

Introduction:

Diamond rectangle segment for drill bits are suitable for drilling cured reinforced concrete green concrete or stone material. Under same bond conditions, the drilling speed of this turbo segments is much faster than normal flat segments.

Features:

1. Higher drilling efficiency.
2. Long lifespan and stable performance.

Specifications:

The followings are the normal specifications of our diamond rectangle segment for drill bits:

Product Name	Diameter	Segment Width	Segment No.	Applications
Diamond rectangle segment for drill bits	2.25"(57mm)	22x3.5x10	5	Concrete Brick Masonry
	2.50"(63mm)	22x3.5x10	6	
	2.75"(70mm)	22x3.5x10	7	
	3"(76mm)	22x3.5x10	8	
	3.25"(82mm)	22x3.5x10	9	
	3.50"(89mm)	22x3.5x10	10	
	4"(102mm)	22x3.5x10	10	
	4.25"(108mm)	22x3.5x10	11	
	4.50"(114mm)	22x3.5x10	11	
	4.75"(120mm)	24x4.0x10	11	
	5"(127mm)	24x4.0x10	11	
	5.5"(140mm)	24x4.0x10	12	
	5.75"(146mm)	24x4.0x10	13	
	6"(152mm)	24x4.0x10	13	
	6.25"(159mm)	24x4.0x10	14	
	6.5"(165mm)	24x4.0x10	15	
	7"(178mm)	24x4.0x10	16	
	8"(203mm)	24x4.5x10	18	
	9"(229mm)	24x4.5x10	20	
	10"(254mm)	24x4.5x10	23	
11"(280mm)	24x5.0x10	25		
12"(305mm)	24x5.0x10	27		
13"(330mm)	24x5.5x10	30		
14"(356mm)	24x5.5x10	32		

The above specifications are for reference, other specifications can be ordered by customers.