

## Introduction:

These diamond laser flat segment blades are mainly used for cutting reinforced concrete, brick, masonry or asphalt, green concrete, sandstone etc.

## Features:

1. Universal dry and wet cutting blades.
2. Fast and smooth cutting, high performance.
3. Wide notch (U gullet) blades are suitable for asphalt green concrete and sandstone.
4. While using specially designed holes in the core improve cooling of the blade and reduce noise.

## Specifications:

The followings are the normal specifications of our diamond laser flat segment blades:

Product Name	Outer Diameter		Segment Width		Arbor	Segment Height	Segment Number	Applications
	inches	mm	inches	mm				
Diamond Laser Flat Segment Blade	4"	105	0.085"	2.2	16/20	8mm	8	Masonry Brick Reinforced Concrete Asphalt
	4.5"	115	0.085"	2.2	22.23	8mm	9	
	5"	127	0.085"	2.2	25.4/50	8mm	10	
	6"	152	0.095"	2.4		8mm	12	
	7"	178	0.095"	2.4		8mm	14	
	8"	203	0.110"	2.8		8mm	16	
	9"	229	0.110"	2.8		8mm	18	
	10"	254	0.110"	2.8		10mm	17	
	12"	305	0.120"	3.0		10mm	21/18	
	14"	355	0.125"	3.2		10mm	24/21	
	16"	406	0.140"	3.6		10mm	28/24	
	18"	457	0.155"	4.0		10mm	32/28	

The above specifications are for reference, other specifications can be ordered by customers.

Note: Wide notch configuration all blades 12" and above.

## Contact Us:

**Fujian Nanan Boreway Machinery Co., Ltd.**

**Address: Huahui Center 605, Shuitou Town, Quanzhou, Fujian, China.**

**Post Code: 362342**

**Tel.: 0086-595-86990206**

**Fax:** 0086-595-86990220

**Contact:** Ally Huang

**Mobile/WhatsApp:** 0086-13559599186

**Wechat:** boreway05

**Skype:** boreway05

**Facebook:** 13559599186

**E-mail:** boreway05@boreway.net

**Website:** <http://www.diamondtools.top>