

Introduction:

These diamond wire and beads are used for wet cutting various kinds of concrete, for removing

large concrete such as bridges, foundations, thick walls etc.

Features:

1. Boreway diamond wire and beads for concrete, universal wet cutting wire for various kinds of concrete.

2. The synthetic rubber adheres extremely well to the beads, wire and spring. This design protects

against wear and prevents slurry from contaminating the spring and wire.

3. These wires can provide very fast, smooth and low noise cutting. The smaller bead diameter also

allows using as a problem-solving wire to finish a difficulty.

Specifications:

The followings are the normal specifications of our diamond wire and beads for concrete:

Diameter	Beads	Attachment	Application	Power	Wire Speed	Efficiency	Cutting Life
mm	pcs/M			kw	m/s	m ² /h	m ² /M
9.5	40	Rubber+Spring	RC	8~25	20~30	1~4	1~5
10.5	40	Rubber+Spring	RC	8~25	20~30	1~3	1~5
10.5	40	Rubber+Spring	ERC	10~35	20~30	1~3	1~5
11	40	Rubber+Spring	ARC	10~35	20~30	0.5~3	1~5

RC: Reinforced concrete; ERC: Extra reinforced concrete;

Class ARC: Abrasive reinforced concrete.

The above specifications are for reference, other specifications can be ordered by customers.