

Introduction:

- 1.D86x30Tx50H Heavy Duty Calibrating Wheel For Marble are used for surface milling and material removal for various granite and marble stone
2. It is been applied to router machines or CNC machines.
- 3.It is used to level off your slab before running your profile wheels.

Feature:

- 1.The unique design with good sharpness allows easy dust removal, low noise and safety.
- 2.With feature of high efficiency,accuracy in shape and size.
- 3.Good performance and long lifespan.

Specification:

Mill milling wheel of the conventional specifications:

Diameter / mm	Segment height / mm	Inner Hole / mm	Connection	Grit NO.	Machine
50 86 100 90	20 30 40	10 50	Φ10-2 + 2Hole Φ50-3 + 3Hole Φ50-3 + 3Hole	30/40 # 60 # 100 # 200 #	CNC machine and radial arm machine

In order to improve the grinding efficiency of grinding wheel, we have some suggestions for the machine speed:


RPM	Feed rate	Recommended depth
4500	400-600mm / min	3mm

Other specifications can be customized after communication

Images:


[Click this link to browse other sizes of diamond standard stubbing wheel:](#)

boreway®




Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

boreway®



NAME: Standard Stubbing Wheel
SIZE: D86×30T×50H
QUANTITY: 1 PC
REMARK:



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Contact us:

Fujian Nanan Boreway Machinery Co.,Ltd.

Address: Huahui Center 605, Shuitou Town,Quanzhou, Fujian, China

Post Code: 362342

TEL: (+86)595-86990206/(+86)18250633812

FAX: (+86)595-86990220

WhatsApp/Wechat: +86-18359335376

Facebook: borewaysherry

Email: boreway02@boreway.net