

Diamond Segments of Drill Bits - Cuspate Top Turbo Shape

Diamond Segments Cuspate Top Turbo shape of drill bits diameter 32mm-356mm provide smooth and fast drilling.

Applications: Cured reinforced concrete with hard to soft aggregates, green concrete or abrasive material.

Welding Type: Silver welding.

Wet Use.

Compared to normal turbo segments, there is a cuspate top on the segments, with this structure initially the drilling speed is very fast.

The following are the normal Specifications we are selling:

Code No.	Diameter	Segment Size	Segment No.
BW-DS-DB-C06-01	2.25"(57mm)	24x3.5x14	5
BW-DS-DB-C06-02	2.50"(63mm)	24x3.5x14	6
BW-DS-DB-C06-03	2.75"(70mm)	24x3.5x14	7
BW-DS-DB-C06-04	3"(76mm)	24x3.5x14	8
BW-DS-DB-C06-05	3.25"(82mm)	24x3.5x14	9
BW-DS-DB-C06-06	3.50"(89mm)	24x3.5x14	10
BW-DS-DB-C06-07	4"(102mm)	24x3.5x14	10
BW-DS-DB-C06-08	4.25"(108mm)	24x3.5x14	11
BW-DS-DB-C06-09	4.50"(114mm)	24x3.5x14	11
BW-DS-DB-C06-10	4.75"(120mm)	24x4.0x14	11
BW-DS-DB-C06-11	5"(127mm)	24x4.0x14	11
BW-DS-DB-C06-12	5.5"(140mm)	24x4.0x14	12
BW-DS-DB-C06-13	5.75"(146mm)	24x4.0x14	13
BW-DS-DB-C06-14	6"(152mm)	24x4.0x14	13
BW-DS-DB-C06-15	6.25"(159mm)	24x4.0x14	14
BW-DS-DB-C06-16	6.5"(165mm)	24x4.0x14	15
BW-DS-DB-C06-17	7"(178mm)	24x4.0x14	16
BW-DS-DB-C06-18	8"(203mm)	24x4.5x14	18
BW-DS-DB-C06-19	9"(229mm)	24x4.5x14	20
BW-DS-DB-C06-20	10"(254mm)	24x4.5x14	23
BW-DS-DB-C06-21			

Contact Us:

Fujian Nanan **boreway** Machinery Co.,Ltd.



No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China



TEL: (+86)595-86990206 /



Fax: (+86)595-86990220



Mobile/WhatsApp/Wechat: (+ 86) 18650679939



E-mail: boreway@boreway.com

