

Introduction:

45s diamond bush hammer roller without support block is used on manual grinding machines or auto/semi-auto bush hammered machines to process bush hammered litchi surface on concrete granite, marble and other stone surface. The processing surface can be very uniform and seems real and natural. The rollers can be changed conveniently, greatly reduced the production costs.

Features:

1. **45s diamond bush hammer roller without support block** for granite has high grinding efficiency and long lifespan.
2. Uniform, real and natural processing surface.
3. Much lower production costs compared with traditional processing method.

Specifications:

The followings are the normal specifications of our **45s diamond bush hammer roller without support block** :

Product Name	Outer Diameter		Roller Quantity	Segment Quantity	Connection
	Inch	mm			
Bush Hammer Plate	5	125	3	30	M14 M16 5/8''-11 42mm 47mm 50mm
	6	150	4	45	
			3	30	
	8	200	6	45	
			4	30	
	10	250	8	45	
			5	30	
	12	300	10	45	
			6	30	

The above specification just a reference for clients. Other specifications can be ordered by customers.

Picture:

45s diamond bush hammer roller without support block

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Related product:

150mm 3 rollers Stone Slab Surface Grinder, Concrete bush hammer for angle grinder

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com