

Introduction:

Normal flat segment for construction diamond core drill bits are suitable for drilling cured reinforced concrete green concrete or stone material. Under same bond conditions, the drilling speed of this turbo segments is much faster than normal flat segments.

Features:

- 1.High quality formula provide higher drilling efficiency.
- 2.Wet or dry drilling.
- 3.Long lifespan and stable performance.

Specifications:

The followings are the normal specifications of our normal flat segment for construction diamond core drill bit:

Product Name	Diameter	Segment Size	Segment No.	Applications

Normal flat segment for construction diamond core drill bits	1.25"(32mm)	16x3.0x10	4	Concrete
	1.38"(35mm)	16x3.0x10	4	Brick
	1.50"(38mm)	16x3.0x10	5	Masonry
	1.63"(42mm)	16x3.0x10	5	
	1.75"(45mm)	16x3.0x10	6	
	1.88"(48mm)	16x3.0x10	6	
	2"(52mm)	16x3.0x10	7	
	2.25"(57mm)	24x3.5x10	5	
	2.50"(63mm)	24x3.5x10	6	
	2.75"(70mm)	24x3.5x10	7	
	3"(76mm)	24x3.5x10	8	
	3.25"(82mm)	24x3.5x10	9	
	3.50"(89mm)	24x3.5x10	10	
	4"(102mm)	24x3.5x10	10	
	4.25"(108mm)	24x3.5x10	11	
	4.50"(114mm)	24x3.5x10	11	
	4.75"(120mm)	24x4.0x10	11	
	5"(127mm)	24x4.0x10	11	
	5.5"(140mm)	24x4.0x10	12	
	5.75"(146mm)	24x4.0x10	13	
	6"(152mm)	24x4.0x10	13	
	6.25"(159mm)	24x4.0x10	14	
	6.5"(165mm)	24x4.0x10	15	
	7"(178mm)	24x4.0x10	16	
	8"(203mm)	24x4.5x10	18	
	9"(229mm)	24x4.5x10	20	
	10"(254mm)	24x4.5x10	23	
	11"(280mm)	24x5.0x10	25	
	12"(305mm)	24x5.0x10	27	
	13"(330mm)	24x5.5x10	30	
	14"(356mm)	24x5.5x10	32	

The above specifications are for reference, other specifications can be ordered by customers.