

Description:

Dry use diamond core drill for granite 1-3/8" are produced by silver or laser welding.

It can be suitable for stand drilling machines or electrical hand-held drillers or CNC machine.

For drilling kinds of granite or hand stone.

Silver welded is better for wet use and laser welded is better for dry use.

Features:

1. Designed for drilling holes
2. Good stable and long lifespan.
3. Can be dry or wet use.

Specifications:

The following is the normal size of **Dry use diamond core drill for granite 1-3/8"**:

| Code No. | Diameter | Segment Size | Use | Pipe Length | Welding Method | Adaptor |
|----------------|---------------|--------------|-----|-------------|----------------|---------|
| BW-DDB-S03 | 20mm (3/4") | 17/12x3x10 | Wet | 4" | Silver Welding | 5/8"-11 |
| | 22mm (7/8") | 17/12x3x10 | or | (100mm) | or | M14 |
| | 25mm (1") | 17/12x3x10 | Dry | | Laser Welding | 1/2 Gas |
| | 29mm (1-1/8") | 17/12x3x10 | | | | |
| | 32mm (1-1/4") | 16x3x10 | | | | |
| | 35mm (1-3/8") | 16x3x10 | | | | |
| | 38mm (1-1/2") | 16x3x10 | | | | |
| | 42mm (1-5/8") | 16x3x10 | | | | |
| | 45mm (1-3/4") | 16x3x10 | | | | |
| | 50/51mm (2") | 16x3x10 | | | | |
| | 57mm (2-1/4") | 22x3.5x10 | | | | |
| | 60mm (2-3/8") | 22x3.5x10 | | | | |
| | 63mm (2-1/2") | 22x3.5x10 | | | | |
| | 70mm (2-3/4") | 22x3.5x10 | | | | |
| | 76mm (3") | 22x3.5x10 | | | | |
| | 80mm (3-1/8") | 22x3.5x10 | | | | |
| | 89mm (3-1/2") | 22x3.5x10 | | | | |
| | 100mm (4") | 22x3.5x10 | | | | |
| 110mm (4-3/8") | 22x3.5x10 | | | | | |
| 127mm (5") | 24x4x10 | | | | | |

The above specification just a reference for customer. Other specification can be ordered by clients.

Picture:

Dry use diamond core drill for granite 1-3/8"