

Introduction:

Segment Diamond Finger Drill Bit For Slab

D20*50T*M14 are usually use after diamond core drill bits,

fast removing dust,diamond sink wheel.

They are

ideal for fast stock removal as well as truing up saw lines, which is designed to cut granite, engineere d

stone and marble,counter tops, kitchen tops and basins.

Usually mounted on CNC or Radial Arm machines, for hole grinding, anchor and blind hole.

Center water feed holes in each bit.

Wet use only.

Feature:

- 1.Faster Speed and Lasting longer
- 2. Less Noise and Low Ampere

Specifications:

The following are the normal specifications about **Segment Diamond Finger Drill Bit For Slab D20*50T*M14** :

Diameter	Bore (mm)	Segment Length	Segment No.
20mm (3/4")	1/2 Gas (Male Thread) M14 5/8"-11	40mm	4-6pcs
25mm (1")		45mm	
30mm (1-1/4")		50mm	
35mm (1-3/8")		60mm	
40mm (1-5/8")			
50mm (2")			
60mm (2-3/8")			

The above specifications are for reference, other specifications can be ordered by customers.

Picture:

Segment Diamond Finger Drill Bit For Slab D20*50T*M14

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Related product:

Shank Diamond Finger Milling Bit With Strength Bottom For Stone D20*40T*12B

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com