Production Description:

Introduction

Diamond calibration roller is most commonly used to calibrate and achieve a uniform thickness on ceramic tiles surface before polishing. Thanks to the continuous technical improvement and the feedback from our customers, our diamond rollers are approved for their good sharpness, long working lifetime, low energy consumption, low working noise, excellent working effect and stable performance.

Wet use only with sufficient water, Fast & Easy grinding, long life, perfect performance.

All of our our products have been strictly tested before access to market.

Other specifications can be customized according to requirements.

Detailed Images:

The following is the normal specification of diamond calibrating rollers:

Product Name	Out Diameter (mm)	Length (mm)	Spiral Number	Segment Size (mm)	Grit (#)
Diamond Calibrating Rollers	Φ180 - Φ320	320	5 6 7 12 16	9*12 9*15 6*10	30 40 50 60 70 80 100 120 140
		400			
		595			
		645 (585)			
		800 (740)			
		800 (680)			
		995 (935)			
		1195 (1135)			
		1600 (1540)			

The following shows only part of the product , other products can be customized according to your needs .

If you do not see the product you want , please contact us for more product images .

Above is a picture of our conventional diamond calibration rollers,
Other specifications can be customized according to requirements.

Packing

We will deliver within seven days of your payment,diamond calibrating rollers are packed in wooden.

We can also pack the rollers according to your requirements.

Special specifications through consultation delivery.

Contact Us:

Fujian Nanan Boreway Machinery Co.,Ltd.

Address: Hongxing Street, Shuitou Town,Quanzhou, Fujian, China,

Post Code: 362342

TEL: (+86)595-86990206/(+86)18250633812

FAX: (+86)595-86990220

WhatsApp:+86-18359335376

E-mail: Boreway05@boreway.net