生□□□□□

導入:

ダイヤモンド校正ローラーは、最も一般的に較正し、研磨前のセラミックタイルの表面に均一な厚さを達成するために使用されます。継続的な技術的な改善や、お客様からのフィードバックのおかげで、私たちのダイヤモンドローラーは長寿命、低消費電力、低動作音、優れた作業効果と安定した性能を働いて、その良好なシャープネスのために承認されています。

十分な水のみ、高速&アンプで濡れ使用。簡単な研削、長寿命、完璧なパフォーマンス。

当社のすべての製品は、厳密には、市場へのアクセスの前にテストされています。

その他の仕様は、要件に応じてカスタマイズすることができます。

詳□□□□□

以下は、ダイヤモンド校正ローラーの正常な仕様です。

商品名	アウト直径（mm）	長さ（mm）	スパイラル数	セグメントサイズ（mm）	グリット（#）
ダイヤモンド キャリブレーション ローラー	Φ180 - Φ320	320	5 6 7 12 16	9 * 12 9 * 15 6 * 10	30 40 50 60 70 80 100 120 140
		400			
		595			
		645（585）			
		800（740）			
		800（680）			
		995（935）			
		1195（1135）			
		1600（1540）			

以下に示す製品の一部のみ、他の製品があなたのニーズに応じてカスタマイズすることができます。

あなたが欲しい製品が表示されない場合は、より多くの製品イメージについてはお問い合わせください。

boreway
ISO 9001
CE
Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

boreway
ISO 9001
CE
Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

boreway
ISO 9001
CE
Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

boreway
ISO 9001
CE
Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

[illegible]

[illegible]

[illegible]

[illegible]7[illegible]

[illegible]

[illegible]

[illegible]

[illegible]**Boreway**[illegible]

[illegible] Hongxing[illegible]Shuitou[illegible]

[illegible] 362342

TEL[illegible] [illegible]86[illegible]595[illegible]86990206 /[illegible]+ 86[illegible]18250633812

[illegible] [illegible]86[illegible]595[illegible]86990220

WhatsApp[illegible]+ 86-18359335376

E[illegible]Boreway05@boreway.net