description:



Diamond Floor Grinding Block With 4 Rectangle Segments

Diamond Concrete Grinding Plates are the best solution for large areas of thin coating removal, leveling and smoothing high spots in concrete, and work very well for concrete cleaning. Their segments are designed for aggressive grinding of concrete to make short work of your larger projects. These High Quality Diamond Grinding Tools are also ideal for the initial steps in concrete polishing procedures.

Specifications:

The general specification Of Diamond Floor Grinding Block With 4 Rectangle Segments:

Name:	Diamond Floor Grinding Block With 4 Rectangle Segments
Block grit:	Coarse, Medium, Fine (16 #, 24 #, 36 #, 46 #, 60 #, 80 #, 120 #, 180 #, 230 #, 270 # etc.).
Section Shape:	4T*40x10x10mm
Block shape shape	4 Rectangle Segments
material:	Diamond + metal powder
Quality:	International standard quality
Connection:	Frankfurt Base
machine:	For quick connecting grinding machine

Specifically designed tools are available for any standard application. We can do it Tailor your equipment to your specific needs.

Product Details:

Diamond Floor Grinding Block With 4 Rectangle Segments:



If you are interested in our products, you can click on me.

Applications:

Diamond Floor Grinding Block With 4 Rectangle Segments

- 1) Combination of superior diamonds and an extremely durable and unique matrix
- 2) Removes stock quickly and efficiently to greatly reduce your product and labor cost
- 3) Lasts much longer than competitive products and will not glaze
- 4) Amazing results on most types of concrete from soft to very hard





Benefit:

- 1) A combination of superior diamonds and a highly durable and unique matrix
- 2) Removes stock quickly and efficiently to reduce its product and labor costs
- 3) Lasts longer than competing products and won't shine
- 4) Surprising results on most types of concrete from soft to very hard

Features:

- 1) Segment size: 4*40x10x10mm
- 2) Segment Shapes: Rectangle
- 3) Grit: Coarse, Medium, Fine(6#,16#,20#,30#,60#,80#,150#,220# etc)
- 4) Bond: Super Soft, Soft, Medium Hard, Hard, Super Hard

related product:



about us:

Company Information

Fujian Nanan BOREWAY MACHINERY Co., Ltd. is the export company. We are professional factory making and various kinds of diamond tools for concrete and stone. Our main products include concrete grinding tools, diamond polishing pads, diamond core drill bits, cup grinding wheels, diamond blades, diamond router bits and drum wheels etc. With our high quality and good service, BOREWAY is gaining more popularity in international trade. We sincerely welcome your inquiry and establish long-term cooperation with us. Thank you

About feedback

Please confirm the products after confirming the receipt.

If you have any questions about the products you received, please contact us and we will do our best to solve this problem and satisfy you.

our service:

- 1.Low order quantity: It can meet the trial order you need.
- 2. Fast delivery: We get great discount from freight forwarders.
- 3. OEM Acceptable: We can produce according to your sample or picture.

4. Good Quality: We have a strict quality control system. Has a good reputation in the market.

5. Good service: We treat our customers as God with a high degree of professionalism and enthusiasm.

description:

Tips: Diamond Bond Choice

Soft Bond - For Hard Concrete, between 4000 and 5500 psi. Bonds needs to be soft to expose diamond crystals to grind the hard surface. Hard concrete contains hard granite, quartz, river stone, flint rock.

Medium Bond - For Medium Concrete, between 2500 and 4000 psi - Suggested in most cases, most popular and most common bond used. For use on floors containing common pit gravel and/or medium river stone, traprock, crushed gravel. The Soft and Hard Bonds are typically reserved for extreme (uncommon) cases.

Hard Bond - For Soft Concrete, typically under 2500 psi. Bond has harder metals in its matrix to withstand the abrasion, so the diamond crystals are not kicked-out before they have a chance to work the surface. Soft concrete contains limestone, sandstone, dolmite, soft shell.

We also offer Super Soft Bond for Extra Hard Concrete, over 5500 psi. And Super Hard Bond for Extra Soft Concrete.

1. If we want to order your product, how do we know your quality?

Please test in very short order and then you will know the quality. now Many people in the world use Chinese products due to their high quality and high quality. Competitive price. We are a professional diamond tool manufacturer. In any case, for more than 8 years, please confirm the quality of our products, small trial orders will be tested Important.

Can you provide samples for free?

We do not provide free samples. Based on years of experience, we believe people will achieve them.

By paying for the sample, we will appreciate the more we get. We would be Be prepared to offer special discounts to our potential customers to participate in the trial. It is very important to give us feedback and we will be very grateful.

3. Does your company accept customization?

Of course, we accept it. Various colors, gravel etc., we can also tag your own logo And brand on board. You want us to create a new product for you, just send us your product. Drawing or sampling, we produce the same. We will not sell such products to others Only customers can get a license.

please pay attention:

1) If you are interested in any item, please let us know what style and patience you want.

Thanks a lot!

2) If we are not on-line, you can give us a message or email. We will see you again in the shortest time possible.

3) Since computer screens have chromatic aberration, SPT screens and LCD screens are spied on.

4) We cannot guarantee that the color of our products will be exactly the same as the pictures you have seen.

Contact us:

Fujian Nanan homeway Machinery Co., Ltd.

🔀 No.605 Huahui Center, Shuitou Town 362342 Quanzhou, Fujian, China

Phone: (+86) 595-86990206 / **Pax:** (+86) 595-86990220

Mobile / WhatsApp / WeChat: (+ +) 13559599186

E-mail: <u>boreway09@boreway.net</u>

Chillin lin