

Introduction:**Concrete Floor Grinding Block With Scerw Hole 3*M6** is

designed specifically for Concrete floor restoration professional, for quick removal of any materials, bonds Hard, Medium, or Soft available for kinds of concrete.

The segment of Diamond Metal Grinding Block Pad is ideal for removing heavy coating. The

segment is extremely aggressive leaving and deep

to medium scratch pattern. The segments remove adhesives, coating and lippage, taking the floor from coarsely structured surface to pre-polishing.

Bond: Hard, Medium, Soft

Features:

1. High aggressive and efficient for various concrete floors.
2. Stable performance and long lifespan
3. Different hardness for different concrete are available upon clients'.

Specifications:

The followings are the normal specifications of our **Concrete Floor Grinding Block With Scerw Hole 3*M6:**

Code No.	Segment Size	Segmen No.	Grit No.	Base Specification
BW-TR-05	40*10*14mm	2	#6, #16, #25, #36, #40, #50, #60, #80, #100, #120, #150, #170, #200	Standard Redi-Lock diamond holder disc

The above specifications are for reference, other specifications can be ordered by customers.

Picture:**Concrete Floor Grinding Block With Scerw Hole 3*M6**



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com

Related product:
Floor Grinding Disc For Concrete

boreway®



Boreway Machinery Co., Ltd.
www.diamondtools.top
www.boreway.com